

Simulations of multiwavelength cladding pumping of high-power fiber Raman amplifiers (Erratum)

Nan Zhao,^{a,b} Soonki Hong,^{a,*} Achar V. Harish,^a Yutong Feng,^a and Johan Nilsson^a

^aUniversity of Southampton, Optoelectronics Research Centre, Southampton, United Kingdom

^bSouth China Normal University, Guangzhou Key Laboratory for Special Fiber Photonic Devices, Guangzhou, China

[DOI: [10.1117/1.OE.59.8.089801](https://doi.org/10.1117/1.OE.59.8.089801)]

This article [Opt. Eng. 58(10), 102701 (2019), doi: [10.1117/1.OE.58.10.102701](https://doi.org/10.1117/1.OE.58.10.102701)] was originally published on 25 September 2019 with an error in Eq. (1). The original Eq. (1) appeared as

$$\frac{dP_i}{dz} = -\alpha_i + \sum_j G_{ij} P_i P_j,$$

which is missing P_i at the loss term $-\alpha_i$. The equation has been corrected to

$$\frac{dP_i}{dz} = -\alpha_i P_i + \sum_j G_{ij} P_i P_j.$$

Online versions of the paper were corrected on 18 August 2020.

*Address all correspondence to Soonki Hong, E-mail: s.hong@soton.ac.uk